

# CHRISTIE GRIFFYN 4K50-RGB

Large-scale events and venues | Rental and staging  
Projection mapping | Sports venues | Theme parks and attractions

## Pure laser. Pure performance. Pure excellence.

A technological marvel, the Christie Griffyn® 4K50-RGB pure laser projector combines superior Christie electronics, our proprietary RGB laser illumination architecture with integrated cooling, and a sealed optical path for reliable illumination performance and capabilities that will impress you.

Ready to illuminate any surface with 50,000 lumens while operating at 55dBA at full brightness, the highly advanced Griffyn 4K50-RGB is designed for demanding large-venue applications on the ground or in the air.

### Design excellence

This powerful all-in-one, omnidirectional projector offers our TruLife+™ electronics platform with all-in connectivity, eliminating the hassle of removable option cards because everything you need is built in. Griffyn also includes our new electronic color convergence (ECC), which allows you to adjust convergence via remote control for easy, picture-perfect color alignment. The Griffyn 4K50-RGB once again raises the bar in RGB pure laser projection performance.

### We thought of everything

- › All-in-one, compact design – No external chillers or lasers and a manageable weight of 197lbs makes it the smallest, lightest brightest 3DLP® RGB laser projector available.<sup>1</sup>
- › Produces an exceptionally wide color gamut, achieving ~98% of the Rec. 2020 color space—more than twice the color of Rec. 709 and 50% more than DCI-P3-capable projectors—for an enhanced audience experience.
- › Christie TruLife+ electronics – Native 4K@60Hz is standard. The Mirage option delivers 4K@120Hz or 4K 3D@60Hz per eye. The Mirage Pro option adds even more capabilities: 2K@240-480Hz and Christie View (simultaneous multi-content viewer)
- › Electronic color convergence (ECC) gives you the ability to select red, green, or blue individually and converge via remote control. No ladder or lift required.
- › 4K lens compatibility – Compatible with all Christie 3DLP ILS4 4K lenses.
- › Christie Twist™ – Built-in image warping and multiprojector blending software.



**CHRISTIE®**

## Technical specifications

## Christie Griffyn 4K50-RGB

Image	brightness	<ul style="list-style-type: none"> <li>• 50,000 ISO lumens</li> <li>• 46,000 ANSI lumens<sup>2,3</sup></li> <li>• In ambient temperatures up to 30°C</li> </ul>
	contrast	<ul style="list-style-type: none"> <li>• 5000:1 On/Off with high-contrast lens</li> </ul>
Display technology	type	<ul style="list-style-type: none"> <li>• Dust-sealed 3DLP® (1.38")</li> </ul>
	resolution	<ul style="list-style-type: none"> <li>• 4096 x 2160 (4K)</li> </ul>
Sound		<ul style="list-style-type: none"> <li>• 46dBA/55dBA<sup>4,5</sup></li> </ul>
Illumination	type	<ul style="list-style-type: none"> <li>• Solid-state RGB (red, green &amp; blue) pure laser</li> </ul>
	performance	<ul style="list-style-type: none"> <li>• 25,000 hours<sup>6</sup></li> </ul>
	color performance	<ul style="list-style-type: none"> <li>• Up to 98% coverage of the Rec. 2020 color gamut</li> </ul>
	field replaceable	<ul style="list-style-type: none"> <li>• Yes</li> </ul>
Orientation		<ul style="list-style-type: none"> <li>• Omnidirectional</li> </ul>
Image processing		<ul style="list-style-type: none"> <li>• Christie TruLife+™ electronics, 1.2Gpx/s</li> </ul>
Frame rates	standard	<ul style="list-style-type: none"> <li>• 24-60Hz</li> </ul>
	optional	<ul style="list-style-type: none"> <li>• Christie Mirage option: 4K@120Hz and 4K 3D@60Hz per eye</li> <li>• Christie Mirage Pro option: all the features of the Mirage option plus 2K@240-480Hz and Christie View simultaneous multi-content viewer</li> </ul>
Inputs	standard	<ul style="list-style-type: none"> <li>• 4 x 12G-SDI</li> <li>• 2 x HDMI 2.0</li> <li>• 2 x DisplayPort 1.2</li> <li>• HDBaseT</li> <li>• Audio out</li> <li>• Fiber (QSFP+) for use with Christie Link Transmitter (1 input/1 output)</li> </ul>
Warping and blending	standard	<ul style="list-style-type: none"> <li>• Christie Twist™</li> <li>• Christie Mystique™ Lite can be downloaded at no extra charge</li> </ul>
	optional	<ul style="list-style-type: none"> <li>• Christie Twist Premium and Twist Pro</li> <li>• Christie Mystique</li> <li>• Christie Guardian</li> </ul>
Multi-projector management	optional	<ul style="list-style-type: none"> <li>• Christie Conductor - monitors/controls up to 256 projectors on a single network and can be downloaded at no extra charge</li> </ul>
Lenses	high brightness	<ul style="list-style-type: none"> <li>• 0.38:1 UST high brightness (ILS4)</li> <li>• 0.72:1 high brightness (ILS4)</li> <li>• 0.9:1 high brightness (ILS4)</li> <li>• 1.13-1.66:1 high brightness (ILS4)</li> <li>• 1.45-2.17:1 high brightness (ILS4)</li> <li>• 1.95-3.26:1 high brightness (ILS4)<sup>7</sup></li> <li>• 2.71-3.89:1 high brightness (ILS4)<sup>7</sup></li> <li>• 3.89-5.43:1 high brightness (ILS4)<sup>7</sup></li> <li>• 4.98-7.69:1 high brightness (ILS4)<sup>7</sup></li> </ul>
	ultra high contrast	<ul style="list-style-type: none"> <li>• 0.72:1 ultra high contrast (ILS4)</li> <li>• 0.9:1 ultra high contrast (ILS4)</li> <li>• 1.13-1.66:1 ultra high contrast (ILS4)</li> <li>• 1.45-2.17:1 ultra high contrast (ILS4)</li> <li>• 1.95-3.26:1 ultra high contrast (ILS4)<sup>7</sup></li> <li>• 2.71-3.89:1 ultra high contrast (ILS4)<sup>7</sup></li> <li>• 3.89-5.43:1 ultra high contrast (ILS4)<sup>7</sup></li> </ul>
Power	line voltage	<ul style="list-style-type: none"> <li>• 200-240 VAC, 19A, 50/60Hz Single phase</li> <li>• Connector: IEC60309 30A</li> </ul>
	power consumption	<ul style="list-style-type: none"> <li>• 3800W max (13,000 BTU/hr)</li> </ul>
Cooling		<ul style="list-style-type: none"> <li>• Liquid, self-contained</li> </ul>
Laser class		<ul style="list-style-type: none"> <li>• Class 1 – Risk Group 3</li> </ul>
Operating environment		<ul style="list-style-type: none"> <li>• 5-40°C (41-104°F)</li> <li>• Relative humidity: 10-80% non-condensing</li> </ul>
Dimensions	size	<ul style="list-style-type: none"> <li>• (LxWxH): 36.3 x 25 x 15" (922 x 635 x 380mm) not including lens</li> </ul>
	weight	<ul style="list-style-type: none"> <li>• 197lbs (89.3 kg)<sup>8</sup></li> </ul>

<sup>1</sup> At time of release - May 2022

<sup>2</sup> D65 white measured at 23°C (73.4°F)

<sup>3</sup> Brightness is reduced up to 30% with the use of a high-contrast lens

<sup>4</sup> 46dBA in quiet fan mode at 23°C, 55dBA in standard fan mode at 23°C

<sup>5</sup> Sound pressure measurement, measuring conditions, and method of notation all comply with ISO7779-1999. Sound level may vary between units

<sup>6</sup> To 50% brightness (results may vary depending on environmental conditions i.e. ambient temperature, humidity, dust, smog, other contaminants)

<sup>7</sup> Requires lens hood extension for Class 1, Risk Group 3

<sup>8</sup> Without lens

For the most current specification information, please visit [christiedigital.com](http://christiedigital.com)

Copyright 2022 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and certain other countries. DLP® and the DLP logo are registered trademarks of Texas Instruments. Performance specifications are typical. Due to constant research, specifications are subject to change without notice.  
CD2799-4K50-data-shee-July-22-EN



**CHRISTIE®**